

INFOPRINT 4247-Z03 MULTIFORM PRINTERS

HIGHLIGHTS

- Fast, quiet, reliable printing at up to 1,100 characters per second¹ on up to 8 part forms
- Rugged design for superior durability in mission critical environments
- Cabinet and pedestal configuration available
- Optional Ethernet with support for IPDS™
- Powerful remote printer management
- Automatic forms loading and thickness adjustment



InfoPrint 4247-Z03

HIGH RELIABILITY—LOW COST OF OWNERSHIP

Designed for high output performance in demanding print environments—from the office to the warehouse—InfoPrint® 4247 industrial strength printers provide professional reliability at a cost of ownership that is surprisingly attractive. With an impressive functional lifetime, low per-page costs, and worry-free operation, impact printers from InfoPrint Solutions Company continue to deliver business value that laser printers simply cannot match. For mission-critical applications where reliability is paramount, or when the cost of printing is a concern, the InfoPrint 4247-Z03 is ready to support core business needs and protect the bottom line.

FAST SPEED, BROAD FUNCTIONALITY

With print speeds up to 1,100 cps¹, and durable metal covers, the InfoPrint 4247-Z03 is built to deliver outstanding performance in the most demanding and rigorous environments. Optional dual front paper paths and heavy-duty 6-pin tractors with motion sensors provide easy forms loading and reliable paper movement to support printing on a wide range of multi-form printing.

BOOST EFFICIENCY WITH POWERFUL REMOTE PRINTER MANAGEMENT

The Remote Printer Management Utility, included with the optional Ethernet controller, gives users visibility to real-time printer status

for every printer on the network, remote configuration of multiple printers simultaneously, and remote full function access to a virtual operator panel.

MAXIMIZE PERFORMANCE WITH SAFE AND EFFECTIVE SUPPLIES

InfoPrint supplies are manufactured specifically for our printers using special formulations to minimize part failures resulting in downtime and maintenance charges. Our supplies are produced under strict quality control guidelines to assure consistency from lot to lot. In addition, supplies are rigorously evaluated so that they will maximize InfoPrint printer performance and are safe for our users and the environment.

ADAPTABLE TO YOUR BUSINESS NEEDS

The combination of paper parking, switching and linking can help you maximize your printing options and increase productivity. The all-points-addressable graphics capability enables quality printing of bar codes, logos, overlays and more. To enable the migration from legacy attachments, the integrated Ethernet card supports IPDS and SNMP. For optimal placement flexibility, pedestal and cabinet configurations are available.

EASY TO USE AND EFFICIENT

Automatic forms loading and thickness adjustment, along with customizable intelligent forms handling, enable highly efficient forms loading and retrieval. Additionally, the user-friendly operator panel features an intuitive design for efficient navigation and a multilingual 2x24 LCD display for easy-to-read menus and messages.

WORLDWIDE SERVICE AND SUPPORT

In addition to the standard warranty, InfoPrint Solutions Company offers comprehensive service and support. For more information, visit:

infoprint.com/support

INFOPRINT 4247-Z03 MULTI-FORM PRINTER

For expanded specifications visit: infoprint.com/4247

Max. Print Speed¹

Model 4247-Z03 cps (at 10 cpi):
Fast draft mode 1100
Data processing mode 800
DP text mode 480
NLQ mode 240

Print options

13.6"/345.44 mm maximum print line
Vertical spacing:
6 or 8 lpi selectable from operator panel for text
3, 4, 6, 8 or 9 lpi selectable under program control for text
1/114" increments under program control available for graphics
Horizontal spacing:
10, 12, 15, 16.7, 17.1 and 20 cpi
10 cpi in Fast draft mode
Proportional spacing is available in DP text and NLQ mode
Bar codes:
Postnet, UPC-A, UPC-E, EAN-13, Code 3 of 9, Code 128, Interleaved 2 of 5, Codabar, MSI and Matrix 2 of 5

INFOPRINT 4247-Z03 MULTI-FORM PRINTER

For expanded specifications visit: infoprint.com/4247

Emulations	Standard: Epson FX, IBM® Proprinter III XL and IBM 2381 Personal Printer and native 4247 mode Optional: Ethernet IPDS: IBM 4224, IBM 4230 and native 4247 mode
Paper handling	Support for two continuous forms paths Dual front tractors Paper parking, switching and linking Automatic forms loading and thickness adjustment
Paper Sizes	Continuous forms: 3" to 17" (76 mm to 432 mm) width, 3" to 24" (76 mm to 610 mm) length
Interfaces	Centronics Parallel, Serial (RS-232C), USB 2.0, Ethernet 10/100 BaseT
Physical characteristics	28.4" x 15.7" x 13.8" (721 mm x 399 mm x 351 mm) (WxDxH), 72.6 lb./32.9 kg (weight)
Environmental conditions	Relative Humidity: 10% to 90% RH Temperature: 50° to 105°F (10° to 40.6°C) Acoustics Printing: 53.9 to 59.7 dBA depending on configuration
Warranty and Maintenance	US, Canada, and Latin America: 3 month warranty: 24x7 Maintenance offering: 24x7 Europe, Middle East, Africa, Asia Pacific: 1 year warranty: 9x5 NBD coverage with upgrades to 24x7 (may not be available in all locations) Maintenance offering: 9x5 NBD and 24x7 (may not be available in all locations) For more information, visit: infoprint.com/support/warranties
Supplies²	20 million character inked ribbon (part number 57P1743)

© Copyright InfoPrint Solutions Company 2008.
All rights reserved.

InfoPrint Solutions Company
6300 Diagonal Highway 002J
Boulder, Colorado 80301-9270
U.S.A.

Printed in the United States of America
July 2008

Ricoh and the Ricoh logo are registered trademarks of Ricoh Co., Ltd. in Japan, other countries or both. IBM and the IBM logo are registered trademarks of International Business Machines Corporation in the United States, other countries, or both. The Ricoh and IBM trademarks are used under license from their respective trademark owners.

InfoPrint Solutions Company is a trademark of InfoPrint Solutions Company, LLC, in the United States, other countries, or both. InfoPrint is a registered trademark of Ricoh Co., Ltd., in the United States, other countries, or both. InfoPrint is used under license from the trademark owner.

References in this publication to InfoPrint Solutions Company products or services do not imply that InfoPrint Solutions Company intends to make them available in all countries in which InfoPrint Solutions Company operates. Any purchase of such products or services will be exclusively governed by the terms of the sales or license agreement applicable to such purchase to the maximum extent allowed by law.

These terms are trademarks or registered trademarks of Ricoh Co., Ltd., in the United States, other countries, or both: InfoPrint, IPDS, and Ricoh.

These terms are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both: IBM.

Other company, product, or service names may be trademarks or service marks of others.

¹ Exact speed varies depending on document complexity, system configuration, software application, driver and printer state.

² These yields are not a guarantee of minimum life and are not covered under warranty, but are provided to assist in supplies planning. Actual usage should be used to establish the life of the supply product in each end user's specific application. Many factors, such as print coverage per page, paper type and size, model type and environmental conditions can affect supply life. To optimize the performance of your InfoPrint Solutions Company impact printer, use only genuine InfoPrint Solutions Company supplies. For more information or to purchase InfoPrint Solutions Company printer supplies, contact InfoPrint Solutions Company or an authorized InfoPrint Solutions Company supplies dealer.

IBM Printer Outlet.Com
1-866-430-6202

Fax for a Quick Quote
817-430-6250

#4247-Z03

Organization _____

Name _____

Phone _____ **Fax number** _____
(area code) (area code)

E-mail _____

Address _____

City _____ **State** _____ **Zip** _____

Please indicate your specifications or requirements:

Additional comments:

